

TECHNICAL INFORMATION @ 20°C AND 24Vdc

	HD408T	HD4V8T
Sensor	Piezoresistive	
Measurement range	10, 20, 50, 100, 200, 500, 1000, 2000 mbar ±10, ±20, ±50, ±100, ±200, ±500, ±1000, ±2000 mbar	
Output signal	4 ... 20 mA	0 ... 10 Vdc standard; 0 ... 5 Vdc, 1 ... 5 Vdc on request
Precision	±0.5 % F.S. @ 20°C	
Resolution	Infinite	
Temperature effects	< 1% F.S., zero; <1% F.S., span from -20°C to +60°C (from -4° to 140°F)	
Time stability	< 1 % F.S. over 6 months at 20°C	
Startup time	1 sec. at 99% of full scale reading	
Response time	< 10 ms until it reaches the stated precision by applying a step pressure level	
Power	8 ... 30 Vdc	16 ... 40 Vdc or 24 Vac with output 0 ... 10 Vdc 10 ... 40 Vdc or 24 Vac with outputs 0 ... 5 Vdc, 1 ... 5 Vdc
Absorption	< 4 mA	20 mA @ 20°C, 24 Vdc
Load resistance	$R_{Lmax} = 727 \Omega$ a 24Vcc $R_{Lmax} = \frac{Vdc-8}{22 \text{ mA}}$	Minimum input resistance 10kΩ
Operating temperature	-20 ... +60°C	
Storage temperature	-20 ... +80°C	
Compatible elements	air and dry gases only	
Overpressure limit	350mbar for the models 10, 20, 50, 100 mbar 3X F.S. for all the other models	
Pressure connection	With Ø 5mm flexible tube	
Electric connection	Screw terminal box	
Case	MACROLON	
Case size	64x58x34	
Protection degree	IP67	




HD 408T..., HD 4V8T... RELATIVE OR DIFFERENTIAL ATMOSPHERIC PRESSURE TRANSMITTERS

The HD408T, HD4V8T are analog output relative or differential atmospheric pressure transmitters; they are used in all those applications where non corrosive air or gas need to be monitored, with pressure fields from 10 mbar to 2000 mbar. The piezoresistive sensor gives extremely precise and stable measurements of the applied differential pressure, with excellent repeatability, low hysteresis, and very good temperature stability.

The output signal of the sensor is conditioned to provide either a current output (model HD408T) or a voltage output (model HD4V8T) linearly proportional to the applied differential pressure.

The transmitters are ready to use as they have been calibrated at the factory. They are used to monitor clean room barometric pressure, to control filters, to measure flows (employment with the Pitot tube), for packing and packaging machines, and to control ventilation.



INSTALLATION

In all models the sensor and electronic parts are housed in a robust case in MACROLON with IP67 degree of protection. Opening the cover, the holes that allow to secure the transmitter's base directly to a panel or a wall, become available. HD408T, HD4V8T can be mounted in any position, the deviation of the zero due to the mounting position is in the worst case (10 mbar range) less than 1% F.S. and can be corrected with an appropriate regulating potentiometer, that can be accessed from outside, for pressures up to 100mbar.

Pressure

MECHANICAL DIMENSIONS

